

Instruction / Installation Sheet 1-Gang Low Voltage Mounting Bracket Part # 60-0021-S

- This product is designed for use with low voltage cables ONLY.
- DO NOT run or pull a TV cord or other electrical cords inside the wall.
- It is a violation of the National Electric Code (NEC) to run power cords or extension cords behind the wall.

Tools Needed

Pencil
Drywall Saw or Utility Knife
Phillips Head Screwdriver

Installation

- Hold the low voltage mounting bracket with the face against the wall in your desired location.
- Use pencil and four corner holes to mark the four corners of the drywall cutout (see fig. 1).
- Use pencil and the bracket to connect the four corner points (see fig. 2).
- Cut along the traced line with a drywall saw or utility knife.
- Insert low voltage mounting bracket into opening. Tighten down each of the two screws. As the wings tighten, they will catch the back of the drywall, securing the plate in place.
- Install any standard low voltage single gang wall plate to the bracket.



Caution:

- Never install low voltage wiring during lightning storms.
- Never touch un-insulated wires or terminals unless the wire has been disconnected at its network interface.
- Use caution when installing or modifying data or telecommunication lines.
- DO NOT alter, change, or disconnect existing telecommunication wires if you are unsure of their purpose or function.
- It is NOT recommended to install this product in close proximity to an electrical service panel to prevent interference from electrical current.

Important Instructions:

- Read and understand all instructions.
- Do not use this product near water, for example near bath tub, wash bowl, kitchen, sink, or laundry tub, in a wet basement, or near a swimming pool.
- SAVE THESE INSTRUCTIONS.

